

# METRIS

## LED DIFFUSED LIGHTING APPLIANCE



**METRIS** is a spotlight with a lighting sandwich composed of a 24 LED module and a high performance optical pix-screen. It is installed in wooden panels with both through and blind holes. The fixing system is quick and does not require any tools.

### METRIS without switch

UFORM CODE	WATT & VOLT	LIGHT COLOUR	FINISH	PER PACK
LG-METRISSATINICKNW	1,6W @ 12Vdc	Natural white	Satin Nickel	1
LG-METRISSATINICKWW	1,6W @ 12Vdc	Warm white	Satin Nickel	1

Led converter not included. To be ordered separately.

### SET METRIS 3X without switch

UFORM CODE	WATT & VOLT	LIGHT COLOUR	FINISH	PER PACK
LG-METRISSATINICKNWX3	3X1,6W @ 230Vac	Natural white	Satin Nickel	Set of 3
LG-METRISSATINICKWWX3	3X1,6W @ 230Vac	Warm white	Satin Nickel	Set of 3



Led converter included.

### METRIS SP SPACER



UFORM CODE	FINISH
LG-STSPACERSP	Satin Nickel

### METRIS OB SPACER


UFORM CODE	FINISH
LG-ANGSPACEROB	Satin Nickel



**Colour appearance** natural white  
**Colour temperature** 4400 K  
**Luminous flux** 150 lm  
**Luminous efficiency** 90 lm/W  
**CRI** Ra ≥ 80



**Colour appearance** warm white  
**Colour temperature** 3200 K  
**Luminous flux** 135 lm  
**Luminous efficiency** 85 lm/W  
**CRI** Ra ≥ 80



### FEATURES

**Material:** technopolymer

**Finish:** satin nickel

**Light source:** LED module for pix-screen light

**Connector:** Micro12


**Wiring:** 2000mm

**Application type:** wall units, under wall cabinets or under shelves


**Installation:** recess



### METRIS SP SPACER



### METRIS OB SPACER



**WARNING:** All light fittings must be fitted by a qualified electrician. Care must be taken where lights are enclosed in a cabinet, ensuring there is adequate ventilation. Light fittings should not be fitted in the vicinity of flammable surfaces.